

CWF Flooring, Inc. Product Data Sheet

Product Name: Corrugated Runner Mat
Surface Configuration: Top – V-Rib Corrugated
Thickness: .1'8" Min. - 1/4" max.
Chemical Resistance: Excellent chemical resistance to many commercial and industrial chemicals. Please call for specific recommendations.

Characteristics	Physical Properties	Test Method
Tensile Strength	7000 psi	ASTM-D-412
Elongation	250%	ASTM-D-412
Moisture Absorbtion	.08%	ASTM-D-412
Post Consumer Content	0%	
Post Industrial Content	90%	

Chemical Resistance

Chemical	Ranking	Chemical	Ranking
Butyl Alcohol	Good	Nitric Acid (dilute)	Excellent
Carbon Tetrachloride	Good	Nitric Acid 30%	Excellent
Chromic Acid (dilute)	Great	Potassium Permanganate(dilute)	Good
Gasoline	Great	Sodium Perborate	Good
Hydrogen Peroxide (dilute)	Good	Sodium Hydroxide	Good
Most Acids	Good	Sulfuric Acid (dilute)	Good
Most alkalis	Good	Water	Excellent

A
CWF Flooring, Inc.
Company

CWF Flooring, Inc. 38325 6th St. East, Palmdale, CA 93550
Tel. 1-661-273-8700, 1-661-273-8701 Fax: 1-661-885-8300
Web: www.CartwheelFactory.Com Email: Sales@CartwheelFactory.com