

WALL PADS

READ THIS DOCUMENT AND ALL OTHER ACCOMPANYING PRODUCT DOCUMENTATION THOROUGHLY BEFORE INSTALLING, USING OR PERMITTING USE OF THIS EQUIPMENT. REQUIRE ALL PERSONS INTENDING TO USE THIS EQUIPMENT, AS WELL AS THOSE INSTRUCTING, ASSISTING OR COACHING OTHERS IN THE USE OF THIS PRODUCT, TO READ THIS DOCUMENT THOROUGHLY BEFORE AUTHORIZING THEM TO ENGAGE IN THOSE OR RELATED ACTIVITIES.

DESCRIPTION

CWF's Wall Pads are mounted on interior walls to provide cushioned impact attenuation surfaces. All consist of rigid 1/2" thick OSB oriented strand board backing, 18oz coated vinyl fabric covering and foam filler. Filler foam is bonded to backing. Vinyl cover is wrapped around foam front and side surfaces of pad, then stapled to backing.

Vinyl cover material is available in these colors: Royal Blue, Red, Green, Orange, Yellow, White, Black, Light Blur, Maroon, Dark Green, Lime Green, Pink, Purple, Grey and Tan.

Two styles--differentiated by foam filler type--are offered.

DIMENSIONS:

Standard Wall Pad width is 24". Four standard heights are offered: 48", 60", 72", and 84". Custom sizes/shapes--to maximum width of 48" x maximum height of 96"--are available as are cut-outs permitting access to power switches, boxes, panels, etc.

STYLE 1 WALL PADS

DESCRIPTION:

STYLE 1 WALL PADS are filled with 1-3/8" thick crosslinked polyethylene.

MATERIALS

- BACKING: 1/2" thick OSB (oriented strand board).
- FILLER FOAM: 1-3/8" thick Crosslinked Polyethylene with a density rating of 2.0 lbs pcf: Complies with Federal Motor Vehicle Safety Standard (FMVSS) 302 for fire retardency and ASTM F2440-04 requirements for indoor wall pads.
- VINYL COVER FABRIC: 18 oz coated vinyl fabric (1000 denier polyester scrim) with a tensile strength of 270x270 lbs/inch and tear strength of 100x90 lbs. Material complies with minimum flame resistance requirements as specified in CHSC Section 13115 and is so certified by the California Fire Marshall (Reg# FA-48006). Material is also UV protected as well as mildew/rot/fungus resistant.

STYLE 2 WALL PADS

DESCRIPTION:

STYLE 2 WALL PADS are filled with 2" thick 200 ILD prime polyurethane.

MATERIALS

- BACKING: 1/2" thick OSB (oriented strand board).
- FILLER FOAM: 2" thick 200 ILD prime polyurethane.
- VINYL COVER FABRIC: 18 oz coated vinyl fabric (1000 denier polyester scrim) with a tensile strength of 270x270 lbs/inch and tear strength of 100x90 lbs. Material complies with minimum flame resistance requirements as specified in CHSC Section 13115 and is so certified by the California Fire Marshall (Reg# FA-48006). Material is also UV protected as well as mildew/rot/fungus resistant.

CWF Flooring, Inc. 38325 6th Street East, Palmdale, CA 93550

Web: www.CartwheelFactory.Com Tel. 1-661-273-8700

SUGGESTIONS & TIPS

WALL PAD INSTALLATION REQUIRED TOOLS

NOTE: READ THESE RECOMMENDATIONS COMPLETELY BEFORE STARTING TO INSTALL OR ASSEMBLE THIS PRODUCT. IF YOU REQUIRE FURTHER INFORMATION, PLEASE CALL OUR OFFICES AT 661-273-8700.

2 CLAW HAMMERS
2 SCREW GUNS
1 LEVEL
1 BOX 1-1/4" SCREWS
1 LADDER
2 TAPE MEASURES
1 LONG TAPE MEASURE
2 FELT PENS
SEVERAL SCREW DRIVERS (BOTH TYPES)
HACK SAW
DRILL
PEN AND PAPER
PENCIL
CAMERA

CWF Flooring, Inc. 38325 6th Street East, Palmdale, CA 93550

Web: www.CartwheelFactory.Com Tel. 1-661-273-8700