

TEMP FLOOR

MODULE SIZE:	WIDTH 6" 1 TILE = 1 SQUARE FOOT LENGTH 24" THICKNESS ¾"
MODULE WEIGHT:	1.1 LBS PER TILE/PER SQUARE FOOT
MATERIAL:	HIGH-IMPACT POLYPROPYLENE CO-POLYMER UV INHIBITORS ADDED.
FIRE RATING:	ASTM E-648 DATA SHEET ATTACHED. EXTENT OF FLAME TRAVEL (MM) 1070 CRITICAL RADIANT FLUX (W/cm sq.) IS 0.08
SUPPORT STRUCTURE:	FLOORING MODULE INCORPORATES MULTI-DIRECTIONAL STRUCTURAL SUPPORT RIBBING, ALLOWING FOR DISTRIBUTION OF WEIGHT LOADS.
WEIGHT LOADING:	27,000 lbs/sqft
GROUND SURFACES:	TEMP FLOOR'S UNIQUE HINGED DESIGN ALLOWS FOR USE ON UNEVEN SURFACES-ON GRASS,SAND GRAVEL,CONCRETE,ASPHALT ICE,SNOW ETC, WITH LITTLE SUB-SURFACE PREPARATION
SHIPPING:	40" x 48" PALLET TEMP FLOOR IS DELIVERED PRE-ASSEMBLED IN 3" x 4" PANELS [12 TILES TO A PANEL] EACH PALLET CAN BE LOADED WITH UP TO 100 PANELS [1200 TILES] OR 1200 SQ.FT. [3" x 4" x 8"] PALLET DIMENSIONS 20' OCEAN CONTAINER 12,000 sq.ft. 40' OCEAN CONTAINER 20,000 sq.ft. 48' TRUCK 24,000 sq.ft. 53' TRUCK 28,800 sq.ft.
FUNCTIONAL FEATURES:	<ol style="list-style-type: none">1. INDIVIDUAL MODULAR PANELS INTERCONNECT EASILY IN 12 sq.ft. SECTIONS2. TEMP FLOOR'S HINGE DESIGN ALLOWS FOR THE MODULES TO BE ROLLED-UP FOR DISASSEMBLY IF SO DESIRED. 6' x 20' ROLLS CAN BE EFFICIENTLY HANDLED.3. EACH TILE FEATURES AN ATTRACTIVE TEXTURED NON-SLIP SURFACE WITH A MULTITUDE OF AERATION HOLES FOR TEMPORARY USE ON GRASS SURFACES.4. EACH TILE INCORPORATES A HALF-MOON NETWORK OF CHANNELS TO FACILITATE WATER FLOW IN RAIN SHOWER CONDITIONS AND/OR TO FACILITATE POWER & COMMUNICATION WIRING.
WARRANTY	5 YEAR WARRANTY AGAINST MANUFACTURER'S DEFECTS UNDER NORMAL USE CONDITIONS.

CWF Flooring, Inc. 38325 6th St. East, Palmdale, CA 93550

Tel. 1-661-273-8700, 1-661-273-8701 Fax: 1-661-885-8300

Web: www.CartwheelFactory.Com Email: Sales@CartwheelFactory.com