



**TEMP FLOOR**

**MODULE SIZE:**                    **WIDTH** 6"                    1 TILE = 1 SQUARE FOOT  
**LENGTH** 24"  
**THICKNESS** 3/4"

**MODULE WEIGHT:**                    1.1 LBS PER TILE/PER SQUARE FOOT

**MATERIAL:**                    HIGH-IMPACT POLYPROPYLENE CO-POLYMER  
UV INHIBITORS ADDED.

**FIRE RATING:**                    ASTM E-648 DATA SHEET ATTACHED.  
EXTENT OF FLAME TRAVEL (MM) 1070  
CRITICAL RADIANT FLUX (W/cm sq.) IS 0.08

**SUPPORT STRUCTURE:**                    TEMPORARY FLOORING MODULE INCORPORATES  
MULTI-DIRECTIONAL STRUCTURAL SUPPORT  
RIBBING, ALLOWING FOR DISTRIBUTION OF WEIGHT LOADS.

**WEIGHT LOADING:**                    27,000 lbs/sqft

**GROUND SURFACES:**                    TEMP FLOOR'S UNIQUE HINGED DESIGN ALLOWS FOR USE ON UNEVEN  
SURFACES-ON GRASS,SAND GRAVEL,CONCRETE,ASPHALT ICE,SNOW  
ETC, WITH LITTLE SUB-SURFACE PREPARATION

**SHIPPING:**                    40" x 48" PALLET  
TEMP FLOOR IS DELIVERED PRE-ASSEMBLED IN 3" x 4"  
PANELS [12 TILES TO A PANEL]  
EACH PALLET CAN BE LOADED WITH UP TO 100 PANELS  
[1200 TILES] OR 1200 SQ.FT. [3" x 4" x 8"] PALLET DIMENSIONS  
20' OCEAN CONTAINER    12,000    sq.ft.  
40' OCEAN CONTAINER    20,000    sq.ft.  
48' TRUCK                    24,000    sq.ft.  
53' TRUCK                    28,800    sq.ft.

**FUNCTIONAL FEATURES:**

1. INDIVIDUAL MODULAR PANELS INTERCONNECT EASILY IN 12 sq.ft. SECTIONS
2. TEMP FLOOR'S HINGE DESIGN ALLOWS FOR THE MODULES TO BE ROLLED-UP FOR DISASSEMBLY IF SO DESIRED. 6' x 20' ROLLS CAN BE EFFICIENTLY HANDLED.
3. EACH TILE FEATURES AN ATTRACTIVE TEXTURED NON-SLIP SURFACE WITH A MULTITUDE OF AERATION HOLES FOR TEMPORARY USE ON GRASS SURFACES.
4. EACH TILE INCORPORATES A HALF-MOON NETWORK OF CHANNELS TO FACILITATE WATER FLOW IN RAIN SHOWER CONDITIONS AND/OR TO FACILITATE POWER & COMMUNICATION WIRING.

**WARRANTY**                    5 YEAR WARRANTY AGAINST MANUFACTURER'S DEFECTS UNDER  
NORMAL USE CONDITIONS.

**CWF Flooring, Inc. 38325 6th St. East, Palmdale, CA 93550**  
**Tel. 1-661-273-8700, 1-661-273-8701 Fax: 1-661-885-8300**  
**Web: www.CartwheelFactory.Com Email: Sales@CartwheelFactory.com**